



**WHEN YOU NEED TO HEAR ABOUT IT –
EVERY TIME A DOOR IS OPENED.....**

**DETEX EAX-500 & EAX-2500 EXIT ALARMS
GIVE LOCAL WARNING OF ANY UNAUTHORISED
USE OF EMERGENCY & EXIT DOORS**



Surface Mount
fits narrow 50mm stiles
EAX-500 Surface mount



Surface mount
complete with
back box
EAX-2500 Surface



Flush Mount
for mounting over
150x150 flush box
EAX-2500 Semi-Flush

DETEX EAX-500 / EAX-2500 are heavy-duty self-contained stand-alone alarms, which can be easily and quickly fitted at any door, regardless of any existing panic hardware or other equipment fitted. Any unauthorized use of the door will sound a warning by means of the internal 95-decibel horn inside the unit, enabling an immediate reaction. The alarm is reset by means of the by-pass key, which can also be used for authorised exit.

For technical details of models and options see next page

Further information on the full range of **DETEX** Loss Control Products and Panic Hardware is available at www.detex.com

FEATURES COMMON TO BOTH **DETEX EAX-500** & **EAX-2500** ALARMS:

- Alarm can be silenced by key
- LED & audible arming indication
- Field selectable indicators on or off
- Loud 95dB internal alarm sounds as soon as door opens
- Programmable (on or off) auto re-arm after 2 minutes
- Internal battery is 9 volt type PP3 (Duracell MN1604 / Rayovac A1604)
- Battery & electronics contained inside tamper-monitored housing
- Manual arming / disarming by key
- Audible low battery alert
- Visual low battery alert
- Works with existing door hardware
- Grey case (black optional ex factory)
- Rugged USA design & manufacture
- Secure threaded key bypass cylinder
- Easy to retro-fit – no special tools needed
- Suitable for LH or RH use

SPECIAL FEATURES

- **EAX-500 Surface mount**
- Alarm is silenced only by key
- Suitable for single door use only
- No wiring or external power required
- Easy mounting - no special tools required
- Narrow enough to fit on 50mm door stiles
- Operates on long-life 9 volt alkaline batteries
- Battery is under locked, tamper-proof cover
- Completely self-contained – no external wiring
- Plastic template for foolproof alignment of contacts
- OPTIONAL: External cylinder for key bypass
- OPTIONAL: P/N 102644 for INSWINGING doors
- OPTIONAL: **MODEL EAX-500W Weatherised version** designed for outdoor use



Measurements

Width	Length	Depth
53 mm	196 mm	60mm

- **EAX-2500 Surface or Semi-Flush Mount**
- Alarm relay output for remote monitoring
- Can be wired to multiple doors using magnetic contacts
- Made to fit over standard double gang flush box
- On-board 9V alkaline backup battery
- Operates on 12-24 volts AC or DC
- Remote bypass compatible



Measurements

	Width	Length	Depth
Surface mount	118 mm	117 mm	76 mm
Flush Mount	118 mm	117 mm	79 mm