

## SMART LOCK CYLINDER

# F430 76 161



**Cylinder can be operated by Pin Code, Smart Tag or Bluetooth!**  
**Suitable for Air B n B, Guest Houses and any application where access dates and times need to be set remotely**

### CAN REPLACE ALL STANDARD EURO CYLINDERS

- Installs in minutes to any standard Euro cylinder lock-body
- NO KEYS, WIRES OR POWER SUPPLY NEEDED.
- **FITTING:** If your cylinder looks like one of these Euro-profile cylinders:
  - Simply remove the retaining screw, remove the existing Euro-profile double or thumbturn cylinder and replace it with this Smart Cylinder!
  - Refit the retaining screw, program the cylinder and test it with the door open. The old lock will operate as it did before – but without the need for keys!



### OPENING THE DOOR FROM INSIDE

Turn the Thumbturn - exit is always unhindered

### OPENING THE DOOR FROM OUTSIDE

- By Pin Code – up to **9 Pin Codes** of 6-12 digits each
- By Temporary Code - with date and time limitations
  - Administrator can generate one 10-digit code via a mobile device and send it the temporary user in advance
- By Smart-Card - **maximum 20 cards**
- By Mobile phone via **Bluetooth - up to 8 users**  
Administrator and users can download the free App

**Ideal for Air B n B or any application where expiry dates and times are needed, and the owner/ administrator cannot be on site to grant access.**

### FEATURES:

- **Valid dates and times can be set by Administrator in advance, and sent to guests.**
- **Access commences and expires on the pre-set times and dates - guests can still exit but cannot re-enter once the door is locked.**
- After unlocking, the cylinder automatically re-locks after the pre-set opening- time  
Opening-time adjustable 5-14 seconds
- 3 x RFID Smart tags supplied (13.56 MHz)  
For extra tags - order F430 76 136 / 016
- 3 x AAA alkaline batteries included - lasts for one year's normal use
- Low battery warning displays well in advance
- If batteries run flat – mobile device or power-bank can be connected to USB port
- Adjustable cylinder length – can be adjusted to suit doors of 55 -100 mm thick
- Weatherproof to IP 44. Waterproof silicone weather-shield sleeve is included