

www.lockshop.co.za  
info@lockshop.co.za  
Fax: 086-523-0411  
Whatsapp (Office hours):  
+27 (0)84-200-1555

**THE LOCKSHOP**  
Everything for Every Door

Distributors of locks, door handles,  
door closers, access control, panic,  
exit and other hardware for doors

Cnr Silver & Gold Streets  
Northgate Estate  
Brooklyn 7405,  
Cape Town  
Tel: +27 (0)21-555-1720

Proud Southern African distributors of **DETEX** alarmed panic hardware since 2001

**DETEX**

**WHEN YOU NEED TO HEAR ABOUT IT –  
EVERY TIME A DOOR IS LEFT OPEN.....**

**DETEX EAX-300 & EAX-300W DELAYED (DOOR-PROP) ALARMS  
SOUND A LOUD WARNING AFTER A PRE-SET TIME  
IF DOORS ARE NOT CLOSED AFTER USE**

Designed for use on doors that are allowed to be used, but not allowed to be left open or wedged / propped open, for security reasons. Keeping doors closed saves heating, cooling & electricity costs

- Can be used on any door regardless of existing hardware or lack of hardware
- 3 Year Limited Manufacturer's Warranty

**Specifications for EAX-300 & EAX-300W**

- Loud 100 dB piezo internal alarm
- Easily surface mounted
- 196 x 54 mm, 60mm deep
- **Field adjustable delay - from 1 sec to 4 minutes before the alarm is activated** (15 secs is the default)
- Supplied with one internal 9v battery (Duracell MN1604 / Rayovac A1604)
- Low battery alert
- Visual 'armed' indicator
- Alarm is silenced automatically when door is closed
- Alarm can be bypassed by authorised users by means of a key
- Options: keyed-alike, master keyed, high security **CISA ASTRAL TEKNO S01** or **CISA C3000 T06** registered key
- Secure tamper resistant housing
- Requires a separate key to change battery
- Plastic template makes for easy fitting
- UL and ANSI listed

"UL Listed Miscellaneous Fire Door Accessory"  
ANSI/BHMA A156.29



**Specifications for EAX-300W  
Weatherised version for use on  
gates or doors that are exposed  
to the weather:**

In most respects identical to the **EAX-300** specifications shown at left – but with specially Weatherized electronics, certified to USA driving rain and salt fog tests

"UL Listed Miscellaneous  
Fire Door Accessory"  
UL1034 - 34 Temperature Section 34  
[Temperature Range -31° F (-35° C) to  
150° F (+66° C)]  
UL1034 - 54 Dust Section 54  
MIL-STD 810F, Method 506.4  
(Driving Rain Test)  
MIL-STD

Available in black  
on special order



Other **DETEX** alarm-only models include **EAX-500** and **EAX-2500**. These models sound an **instant alarm** whenever the door is opened and also have a key bypass for the alarm. Weatherised versions for external use are also available.

**We UNDERSTAND locks, and can advise on the broadest range of panic hardware,  
locking hardware & access control equipment**

**Ask the Loxperts - we have over 100 years' experience.**