

Proud Southern African distributors of **DETEX** alarmed panic hardware since 2001

DIGITAL ELECTRONIC LOCK for LOCKERS & CABINETS

No morticing – designed for quick and easy surface mounting inside lockers, cabinets, and containers - with hinged or sliding doors.

Self-contained and battery operated – no external wires or power supplies

Can be programmed to operate with PIN code, cards, tags, or wristbands



F430 76 002 Digital Cabinet Lock



F430 76 003 Locking staple A



Typical Sliding Door operation



F430 76 004 Locking staple B



Typical hinged Door operation

OPERATION:

PRIVATE MODE:

Unlocks with the user's PIN code, card, tag, or wristband

GUEST /PUBLIC MODE: (Gym Locker applications)

The locker is by default left UNLOCKED / OPEN

Card Operation: The guest / user locks the locker, using his/her own Mifare card (credit card, new SA ID card), tag or wristband.

The **same** card, tag or wristband must then be used to open it again.

The locker is then ready for the next user.

Code Operation: The guest / user locks the locker, using his/her own pin code.

The same pin code must then be used to open it again.

The locker is then ready for the next user.



PIN Nos, cards, tags, or wristbands can be deleted and added using the Admin card

- No keys or tags need be issued if keypad-only operation is preferred
- Stand-alone – no network, wires or power supplies needed
- Battery operated by 4 x 1.5V AAA alkaline batteries (6 volts), standby life 12 months
- Low voltage alarm when voltage below 4.5 volts. Will remain unlocked when power drops below 4 volts
- Micro USB port for emergency power supply (power bank) if internal batteries fail
- Mifare Card Technology 13.65 MHz, accepts credit cards and new South African ID cards
- Optional RFID tags, cards, or wrist-bands
- Card reader range: 25 – 40 mm
- Lock holding strength 150 Kgs
- Unlocks automatically when correct card or tag is offered, or correct pin-code is inserted – there is **no need to pull the door!**
- Dimensions: Keypad: 65 x 65 mm Lock: 80 x 80 x 27 mm. Locking staple: (type A) 80 x 27 x 20 mm