



## WHEN YOU NEED TO HEAR ABOUT IT – EVERY TIME A DOOR IS OPENED.....

### DETEX EAX-500 & EAX-2500 EXIT ALARMS

- SOUND AN IMMEDIATE ALARM**  
**- WARNING OF ANY UNAUTHORISED USE**  
**OF FIRE AND EMERGENCY EXIT DOORS**  
**- without impeding escape!**



Surface Mount  
fits narrow 50mm stiles  
**EAX-500 Surface mount**



Surface mount  
complete with  
back box  
**EAX-2500 Surface**



Flush Mount  
for mounting over  
150x150 flush box  
**EAX-2500 Semi-Flush**

**DETEX EAX-500 / EAX-2500** are heavy-duty self-contained stand-alone alarms, which can be easily and quickly fitted at any door, regardless of any existing panic hardware or other equipment fitted. Any unauthorized use of the door will sound an instant warning by means of the internal 95-decibel horn, enabling an immediate reaction. The alarm is reset by means of the **by-pass key, which can also be used for authorised exit - without sounding the alarm.**

#### OPTIONAL EXTRAS

- Keyed-alike and Master-keyed cylinders for the alarm-by-pass
- **CISA ASTRAL TEKNO S01** and **CISA C3000 T06** high security keys
- Specify **DETEX EAX-300** for a **delayed alarm** (when door fails to close after pre-set time).

**For more details of models and options see next page**

Further information on the full range of **DETEX** Loss Control Products and Panic Hardware is available on request or at [www.lockshop.co.za](http://www.lockshop.co.za)

**FEATURES COMMON TO BOTH DETEX EAX-500 & EAX-2500 ALARMS:**

- Alarm can be silenced by key
- LED & audible arming indication
- Field selectable indicators on or off
- Loud 95dB internal alarm sounds as soon as door opens
- Auto re-arm after 2 minutes Programmable (on or off)
- Internal battery is 9-volt type PP3 (Duracell MN1604 / Rayovac A1604)
- Battery & electronics contained inside tamper-monitored housing
- Manual arming / disarming by key
- Audible low battery alert
- Visual low battery alert
- Works with existing door hardware
- Grey case (black optional ex factory)
- Rugged USA design & manufacture
- Secure threaded key bypass cylinder
- Easy to retro-fit or add-on – no special tools needed
- Suitable for LH or RH use

**SPECIAL MODEL-FEATURES**

- **EAX-500 Surface mount**
- Alarm is silenced only by key
- Suitable for single door use only
- No wiring or external power required
- Easy mounting - no special tools required
- Narrow enough to fit on 50mm door stiles
- Operates on one long-life 9-volt alkaline battery
- Battery is under locked, tamper-proof cover
- Completely **self-contained – no external wiring**
- Plastic template for foolproof alignment of contacts
- OPTIONAL: P/N 102644 for INSWINGING doors
- OPTIONAL: **MODEL EAX-500W Weatherised version** designed for outdoor use



Measurements

Width	Length	Depth
53 mm	196 mm	60mm

- **EAX-2500 Surface or Semi-Flush Mount**
- Alarm relay output for remote monitoring
- Can be wired to multiple doors using magnetic contacts
- Made to fit over standard double gang flush box
- On-board 9V alkaline backup battery
- Operates on 12-24 volts AC or DC
- Remote bypass compatible



Measurements

	Width	Length	Depth
Surface mount	118 mm	117 mm	76 mm
Flush Mount	118 mm	117 mm	79 mm